

SHEERFILL® II with EverClean®

SHEERFILL® Architectural Membrane is the original permanent tensioned membrane. SHEERFILL® II has become the standard by which other materials are measured and it offers an excellent balance of strength and light transmission.

EverClean® Photocatalytic Topcoat provides enhanced self-cleaning properties, helping to keep the membrane whiter and brighter while further reducing the already low maintenance requirements of the PTFE coating. In addition, EverClean® helps to clean the air through the reduction of SO_x and NO_x atmospheric pollutants.

All SHEERFILL® membranes conform to rigid fire and building codes for permanent structures.

Typical Properties

Property	Value	Test Method
Coated Fabric Weight (g/m ²)	ca. 1305	DIN 53352
Tensile Strength (N/5cm)		
Warp	7000 min. avg.	DIN 53354
Fill	6000 min. avg.	
Trap Tear Strength (N)		
Warp	500 min. avg.	DIN 53363
Fill	500 min. avg.	
Adhesion (N/5 cm)	100 min. avg.	DIN 53357
Translucency at 550 nm (%)	ca. 12	-
Solar Reflectance at 550 nm (%)	74 nominal	
Fire Testing	B-s1-d0	EN 13501
Burning Characteristics		
Flame Spread	5 max	ASTM E84
Smoke Generation	10 max	Tunnel Test
Incombustibility of Substrates	Pass	ASTM E136
Fire Resistance of Roof Coverings		
Spread of Flame & Intermittent Flame	Class A	ASTM E108
Flame Resistance	Pass	NFPA 701, Small Scale
Color	White (after exposure to sunlight)	-

Values listed are for virgin roll goods only. Appropriate industry safety factors need to be used to account for the in-service effects of handling, weathering, etc. Product specifications are subject to change. Please consult with Saint-Gobain to confirm latest version of this data sheet.

Solar properties are for fully sun-bleached material.

Saint-Gobain Performance Plastics
701 Daniel Webster Highway
Merrimack, NH 03054
Customer Service: +1 800 451 6101
Telephone: +1 603 424 9000

sheerfill@saint-gobain.com

www.sheerfill.com

SHEERFILL® is a registered trademark
©2019 Saint-Gobain Performance Plastics Corporation

IMPORTANT: It is the user's responsibility to ensure the suitability, fitness and safety of Saint-Gobain Performance Plastics products for all intended uses and that the components to be used comply with all applicable regulatory requirements. Saint-Gobain Performance Plastics assumes no responsibility or liability for any advice furnished by it or for any product failures that occur due to installation or misuse arising out of the design, fabrication or application of the products into which they are incorporated.

Limited Warranty: Please see the limited warranty available from Saint-Gobain Performance Plastics for details of warranty coverage for the specific SHEERFILL product. If you have questions about the limited warranty, please contact Saint-Gobain Performance Plastics as referenced above.

Valid 11/2019 - Supersedes all previous versions
PDS.SFIIEC(DIN).1119.CFMC