

SHEERFILL® Ultralux

SHEERFILL Architectural Membrane is the original permanent tensioned membrane. SHEERFILL Ultralux offers the highest light transmission of any of our wide width PTFE coated fiberglass membranes, allowing even more light to fill the space below.

All SHEERFILL membranes conform to rigid fire and building codes for permanent structures.

Typical Properties

Property	Value	Test Method
Coated Fabric Weight (oz/yd ²)	35 nominal	ASTM D4851-88
Thickness (in)	0.030 nominal	ASTM D4851-88
Breaking Strength (lb/in) Strain Rate: 2 in/min		
Warp	675 min. avg.	ASTM D4851-88
Fill	600 min. avg.	
Breaking Strength (lb/in) After Crease Fold		
Warp	525 min. avg.	ASTM D4851-88
Fill	425 min. avg.	
Trapezoidal Tear (lb)		
Warp	75 min. avg.	ASTM D4851-88
Fill	75 min. avg.	
Solar Transmission (%)	21 nominal	ASTM E424
Solar Reflectance (%)	68 nominal	ASTM E424
Burning Characteristics		
Flame Spread	0 max	ASTM E84
Smoke Generation	0 max	Tunnel Test
Incombustibility of Substrates	Pass	ASTM E136
Fire Resistance of Roof Coverings Spread of Flame & Intermittent Flame	Class A	ASTM E108
Flame Resistance	Pass	NFPA 701, Small Scale
Color	White (after exposure to sunlight)	-
Reinforcement Construction	Warp β150 2/4 Fill β150 2/4	Count W19 x F16.5

Values listed are for virgin roll goods only. Appropriate industry safety factors need to be used to account for the in-service effects of handling, weathering, etc.

Saint-Gobain Performance Plastics
701 Daniel Webster Highway
Merrimack, NH 03054
Customer Service: +1 800 451 6101
Telephone: +1 603 424 9000

sheerfill@saint-gobain.com

www.sheerfill.com

SHEERFILL® is a registered trademark
©2018 Saint-Gobain Performance Plastics Corporation

IMPORTANT: It is the user's responsibility to ensure the suitability, fitness and safety of Saint-Gobain Performance Plastics products for all intended uses and that the components to be used comply with all applicable regulatory requirements. Saint-Gobain Performance Plastics assumes no responsibility or liability for any advice furnished by it or for any product failures that occur due to installation or misuse arising out of the design, fabrication or application of the products into which they are incorporated.

Limited Warranty: Please see the limited warranty available from Saint-Gobain Performance Plastics for details of warranty coverage for the specific SHEERFILL product. If you have questions about the limited warranty, please contact Saint-Gobain Performance Plastics as referenced above.

Valid 07/2018 • Supersedes all previous versions
PDS.SFULTRALUX(ASTM).0718.CFM